



2	1	1	1	1
BUTTONS	COMMAND SIGNAL	CONNECTOR	MATING CONNECTOR	INSTALLATION LOCATION
6 ROUND BUTTONS 2 BY 3 STAGGERED LAYOUT SWITCH PANEL	CAN J1939	MOLEX 39-20-2052	MOLEX 39-01-4051	OUTSIDE- POTTED

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		ORIGINATED BY: KJOHNSON	<p>GLOBAL RESOURCES MUKWONAGO, WI 53149</p>
WIRE LENGTH TOLERANCES SPEC = IPC/WHMA-A-620B		ORIGINATION DATE: 6-24-2019	
THIRD ANGLE PROJECTION		PROJECT ENGINEER:	
- FRACTIONS ± 1/16in ± 1.59mm - TOLERANCES ON DECIMALS: 1 PLACE 2 PLACE 3 PLACE in ±.030 ±.010 ±.005 mm ±.76 ±.25 ±.13 - ANGULAR DIMENSIONS ± 1 DEG - REMOVE BURRS - BREAK EDGES 0.01in 0.25mm MAX - MAX SURFACE ROUGHNESS 12.5		ACCOUNT MANAGER:	
MATERIAL:		MATERIAL:	
COATING/PLATING:		CUSTOMER PART NUMBER:	
ALL TECHNICAL DATA ON THIS DRAWING IS THE PROPERTY OF GS GLOBAL RESOURCES INC. AND SHALL NOT BE USED BY OTHERS FOR MANUFACTURE, PROCUREMENT, OR DISCLOSURE WITHOUT THE WRITTEN PERMISSION OF GS GLOBAL RESOURCES INC.		SHIT SIZE: DRAWING NUMBER: B DRAWING REFERENCE: GS17122-002 SCALE: 1:1 SHEET INFO: 1 OF 1	

TITLE BLOCK REVISION DATE: 10-9-2018