BUTTONS	COMMAND SIGNAL	CONNECTOR	MATING CONNECTOR	INSTALLATION LOCATION
6 BUTTON AND 8 ROCKER SWITCH PANEL	CAN J1939	DT06-4S-C015 DT06-6S-C015	DT04-4P DT04-6P	CAB







UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

WIRE LENGTH TOLERANCES SPEC.= IPC/WHMA-A-620B

≤ 1ft	+1in -0in
> 1ft-5ft	+2in -0in
> 5ft-10ft	+4in -0in
> 10ft-25ft	+6in -0in
> 25ft	+5% -0%

THIRD ANGLE PROJECTION

- FRACTIONS ± 1/16in ± 1.59mm
- TOLERANCES ON DECIMALS:

	1 PLACE	2 PLACE	3 PLACE
in	± .030	± .010	± .005
mm	± .76	± .25	± .13

- ANGULAR DIMENSIONS ± 1 DEG
- REMOVE BURRS
- BREAK EDGES 0.01in 0.25mm MAX
- MAX SURFACE ROUGHNESS 125

ORIGINATED BY: KJOHNSON
ORIGINATION DATE: 7-3-2019
PROJECT ENGINEER:
ACCOUNT MANAGER:
MATERIAL:
COATING/PLATING:
CUSTOMER PART NUMBER:

ALL TECHNICAL DATA ON THIS DRAWING IS THE PROPERTY OF GS GLOBAL RESOURCES INC. AND SHALL NOT BE USED BY OTHERS FOR MANUFACTURE, PROCUREMENT, OR DISCLOSURE WITHOUT THE WRITTEN PERMISSION OF: GS GLOBAL RESOURCES INC.

GLOBAL RESOURCES
MUKWONAGO, WI 53149

DRAWING TITLE:
6 BUTTON AND 8 ROCKER SWITCH PANEL WITH DUAL USB PORTS

SHT SIZE	DRAWING NUMBER	REV
B	GS17122-037	A

DRAWING REFERENCE: -
SCALE: 1:2
SHEET INFO: 1 OF 1

TITLE BLOCK REVISION DATE: 10-9-2018