

# CM2115

## Controller Module



<b>General</b>	
Weight	1.0 kg
Operating temperature	-40°C to +85°C
Storage temperature	-55°C to +125°C
<b>Electrical</b>	
System voltage	12 V and 24 V
Operating voltage	6 V to 32 V
Micro core capabilities	Micro type Freescale MPC5534 @ 80 MHz Flash size <sup>1</sup> 1 MB RAM size <sup>1</sup> 128 kB (64kB internal + 64kB external) EEPROM size 32 Kbyte
Communication channels	2 (1 with "Wake on CAN" functionality)
Inputs	Digital inputs 4 x programmable active high or active low 5 x programmable active low Analog inputs 2 x active high "wakeup" inputs Frequency inputs 8 (2 x amplified, 6 x attenuated) Maximum frequency 2 (1 x AC coupled, 1 x DC coupled) 10 kHz
Outputs	High side outputs 6 x 10 A 2 x 5 A 2 x 5 A with accurate current sensing 2 x 2.5 A with accurate current sensing Maximum PWM frequency 500 Hz Low side outputs 1 x 2.5 A with accurate current sensing Maximum PWM frequency 1500 Hz Solid state relay outputs 2 x 1 A
Reference voltage (sensor supply)	1 x selectable 5 V/8 V @ 300 mA
Maximum module current	80 A
Status LEDs	Not on standard unit
<b>Mechanical</b>	
Enclosure Material	Plastic and aluminum
Connector Type	4 x 12 pins, 3 x 1 pins, 51 pins total Deutsch DT series
Mounting Method	Four 1/4" or 6mm bolts

1) total product memory, not all is available to the application.



Foremost in Machine Performance for Life

GS Global Resources • 1-800-261-8735 • [gsglobalresources.com](http://gsglobalresources.com)  
926 Perkins Drive, Mukwonago, WI 53149

© GS GLOBAL RESOURCES, INC. ALL RIGHTS RESERVED.

YOUR SUCCESS.

<b>Software</b>	
Software environment Platform framework	Provides the application developer with the drivers required to access the hardware
Software Development Kit (SDK)	Provides the interface between the platform framework and the application software
Application software	Matlab Simulink (can be developed by the OEM or Parker)
<b>Environment</b>	
Humidity (soak)	ASAE EP455_Feb_2008_section 5.13.1
Humidity (cyclic)	ASAE EP455_Feb_2008_section 5.13.1
Dust/Water Ingress Protection	IP66, 60529 IEC Edition 2.1 2001-02 section 13.6.1 and section 14.2.6
Salt spray	J1455 (Aug 94) Section 4.3.3
Vibration, shock	ASAE EP455_Feb_2008_section 5.14.1
Vibration, random	SAE J1455_Jun_2006_section 4.10.4.2 Figure 10
ESD	ANSI/ASAE EP455_Feb_2008_Section 5.12.2
EMC	
Susceptability Emissions	ANSI/ASAE EP455_Feb_2008_Section 5.16.3/ISO 14982/SAE J1113-41 ISO 14982/SAE J1113-41
<b>Ordering</b>	
Ordering part number	0935024ECD

## Dimensions

